) S	SEC. CL. O	RIGIN		1	CONTROL N	0.
					D-758-6	57
	TE REC'D	DATE OUT	SUSPEN	SE DATE	CROSS REF	ERENCE OR
16 March					, care	·······································
TO Chief.]	Exploit	ation Sy	stem Bra	anch		
FROM SUBJ.	ROUTING	DATE				
Proposal: Advanced Stereo]	inmar
Rhomboid Model II					Ch/ESB	28 MARE
						<u> </u>
						
COURIER NO.	ANSWER	ED	NO REPLY			
						1/

NPIC/TDS/D-758-67 16 March 1967

MEMORAND	UM F	OR: Chief, Exploitation Systems Branch	
SUBJECT		: Proposal: Advanced Stereo Rhomboid Model II	25X1
l. proposal Stereosc	for	lowing is an evaluation of the an Advanced Stereo Rhomboid designed for the Zoom 70	25X1 25X1
	a.	Conformity with Development Objectives - The proposed "Double Arm Rhomboid" most nearly meets our requirements for an improved version of the Model I Wide Span attachment currently in production. The proposed Model II meets or exceeds the various specifications contained in our Development Objectives, and though a bit more expensive than the "Single Arm" version the added versatility outweighs the difference in cost.	
	b.	Design Features - The design of the system is well thought out and has some ingenious features but the overall concept is slanted largely towards the "modular design concept" envisioned for future product development. This has resulted in one feature which probably will not be acceptable to some, namely, having the image rotation performed at the eyepiece rather than at the objective. This would result in a PI having to change a habit pattern when using the new rhomboid if he has been used to using the Model I but there is not much technical	25X1
		justification for not having the adjustment at the eye- piece. From point of view this same feature will per- mit them to guarantee a maximum image runout during im- age rotation of 0.5mm. This figure is not easily and therefore, not economically attainable if the rotation element is located at the objective of the instrument. This is being proven out with the Model I pre-production unit	25X1

Approved For Release	2006/14/30-16/A-RDP78B04	.770A000100080006-8
	2006/14/RP-GYERPP7AB04	

SUBJECT:		Proposal: Advanced Stereo Rhomboid Model II	25X1
		This becomes a trade-off situation. Are we willing to forego the "advantage" of image rotation at the objective for the "advantage" of closer image run-out specifications? My personal opinion is that we should. Except for this one consideration, the total design of the Double Arm Rhomboid is completely satisfactory technically and has a good deal of merit from a human engineering standpoint.	
	c.	Summary - The proposed advanced stereo rhomboid system offers an acceptable design fulfilling the specifications contained in our Development Objectives. It also offers, through modular concept, the opportunity to phase-in this development with our current Zoom 70 complement and at the same time to convert to the Advanced Zoom 70 whenever we wish. This, of course, commits us to stereomicroscope for some time but I feel that it is to our advantage as well as theirs at this time.	25X1 25X1
	d.	production of a prototype "Double Arm" rhomboid as described in their proposal for the following reasons: 1) The design meets all our requirements. 2) It will extend the useful life of our	25X1
		present Zoom 70's. 3) It is adaptable to the improved "Ad-vanced Zoom 70" to be produced by Production costs are reasonable.	25X1
		5) The unit will be useable with the Twin Light Source Table. 6) is the sole bidder.	25X1 25X1
Distribu	tion	ESB	25X1
Orig - 1 -	Ch/	<u>'ESB</u>	25 X 1

CONFIDENTIAL